

SINAN

SE-264

Emergency Light
Thermoplastic Housing
Round Heads



DESCRIPTION

The SE-264 is an economical, double headed emergency lighting fixtures. It has an aesthetically appealing low profile and is quick and simple to install.

APPLICATION

Suitable for use in almost any commercial or light industrial application.

OPTIONS

UL damp location listing. Add "D" to end of catalog number.
Halogen lamps, 5W, 6V JC bipin.
Add "H" to end of catalog number.

APPROVALS

UL924.
UL listed for damp locations.
Life Safety NFPA 101.

HOUSING

The housing is made of injection molded thermoplastic. It has high impact resistance and is UL94-5V rated.

MOUNTING

The back mounting plate is made of injection molded thermoplastic. It has a molded in universal J-Box mounting pattern and keyhole slots. The main housing snaps on to the back plate for quick and easy installation.

LENS

Computer designed optical prisms throw the light outward and to the sides for maximum utilization.

ELECTRICAL/BATTERY

- Dual voltage input 120/277 VAC, 60 Hz.
- Maintenance free, Sealed Lead Calcium 6V, 4.2 AH battery with a maximum full recharge time of 48 hours. Minimum 1 ½ hour emergency operation.
- Low voltage disconnect of the battery prevents deep discharge and maintains good battery life.
- Fully automatic, solid state charger.
- Test switch with LED charge indicator/AC voltage indicator.
- Line latching feature prevents the unit from turning on during installation to a non-energized AC circuit. Saves labor since the installer does not have to return to connect the battery terminals once the building is energized.

Catalog Number	Heads	Lamp Type	Lamp V DC	Lamp Watts	Weight (Lbs)	Volume (cu. ft.)	Pieces Per Skid	Pieces Per 20'	Pieces Per 40'
SE-264L	Round Heads	T-5 Incan.	6	2 x 5.4	4.0	0.23	288	2880	5760
SE-264Q	Square Heads	T-5 Incan.	6	2 x 5.4	3.8	0.16	420	4220	8440